

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 5/45	A1	(11) International Publication Number: WO 98/27725 (43) International Publication Date: 25 June 1998 (25.06.98)
(21) International Application Number: PCT/US97/22750 (22) International Filing Date: 10 December 1997 (10.12.97) (30) Priority Data: 08/770,770 19 December 1996 (19.12.96) US (71) Applicant: THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290-1024 (US). (72) Inventors: RUMREICH, Mark, Francis; 10308 Indian Lake Boulevard South, Indianapolis, IN 46236 (US). ZUKAS, Mark, Robert; 5725 South Walcott Street Rear, Indianapolis, IN 46227 (US). (74) Agents: TRIPOLI, Joseph, S. et al.; GE & RCA Licensing Management Operation, Inc., P.O. Box 5312, Princeton, NJ 08543 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: METHOD AND APPARATUS FOR POSITIONING AUXILIARY INFORMATION PROXIMATE AN AUXILIARY IMAGE IN A MULTI-IMAGE DISPLAY		
(57) Abstract <p>Method and apparatus for generating a signal representing a multi-image video display including a main image (200) and an auxiliary image (202), e.g., a picture-in-picture (PIP) image, provides for positioning auxiliary information, such as closed caption text, proximate the auxiliary image. The auxiliary information (208) is located within a border region (206) for the auxiliary image and positioned for indicating to a user that the auxiliary information is associated with the auxiliary image. The region containing the auxiliary information moves in response to movement of the auxiliary image such that the auxiliary information remains proximate the auxiliary image.</p> <div data-bbox="544 1123 1356 1648"><p>The diagram illustrates a multi-image display system. A large rectangular frame, labeled 200, represents the main image. Within this frame, there is a smaller rectangular area, labeled 202, which represents an auxiliary image. Inside the auxiliary image area 202, there is a specific region, labeled 210, which is the auxiliary image itself. Below the auxiliary image region 210, there is a border region, labeled 206, which contains two rows of 'X' characters, labeled 208. These 'X' characters represent auxiliary information, such as closed caption text, positioned proximate to the auxiliary image. A label 204 points to the top right corner of the auxiliary image area 202.</p></div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD AND APPARATUS FOR POSITIONING AUXILIARY INFORMATION
PROXIMATE AN AUXILIARY IMAGE IN A MULTI-IMAGE DISPLAY

5 CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to the following commonly-assigned U.S. Patent Applications: Serial No. 08/769,329 entitled "TELEVISION APPARATUS FOR SIMULTANEOUS DECODING OF AUXILIARY DATA
10 INCLUDED IN MULTIPLE TELEVISION SIGNALS", Serial No. 08/769,333 entitled "VIDEO SIGNAL PROCESSING SYSTEM PROVIDING INDEPENDENT IMAGE MODIFICATION IN A MULTI_IMAGE DISPLAY", Serial No. 08/769,331 entitled "METHOD AND APPARATUS FOR PROVIDING A MODULATED SCROLL RATE FOR TEXT DISPLAY", and Serial No. 08/769,332
15 entitled "METHOD AND APPARATUS FOR REFORMATTING AUXILIARY INFORMATION INCLUDED IN A TELEVISION SIGNAL", all of which were filed in the name of Mark F. Rumreich et al. on the same date as the present application.

20 FIELD OF THE INVENTION

The invention relates to television receivers capable of generating a multi-image display having main and auxiliary images such as picture-in-picture (PIP) or picture-outside-picture (POP) displays. More particularly, the invention relates to a method and apparatus for
25 displaying auxiliary information, such as closed caption information, proximate an auxiliary image in a multi-image display.

BACKGROUND

A television signal may include auxiliary information in
30 addition to video program and audio program information. For example, an NTSC (National Television Standards Committee) television signal may include two bytes of closed captioning data during the latter half of each occurrence of line 21 of field 1. Closed caption data may be decoded and displayed to provide a visible text representation of a television
35 program's audio content. Additional closed caption data and other types of similarly encoded auxiliary information, such as extended data services information (XDS), may be included in other line intervals such as line 21 of field 2. United States law requires caption decoders in all television

receivers having displays larger than 13 inches and most television programming (including video tapes) now includes captioning data.

Although captioning was developed to aid the hearing impaired, captioning can also provide a benefit to non-hearing impaired viewers as well. Captioning for a multi-image display such as picture-in-picture (PIP) or picture-outside-picture (POP) displays is an example of this type of additional benefit. For example, activating a PIP feature produces an auxiliary image representing the video content of a secondary television program signal. The auxiliary image is a small picture that is inset into a portion of the main picture. However, only the audio program associated with the main picture is processed and coupled to the speakers of the television. The audio content of the secondary signal is lost. Because the audio program is important to the comprehension of a television program, the usefulness of a multi-image display feature such as a PIP display is severely limited by the lack of an associated audio program. An approach to solving this problem is to display captions, i.e., visible text, representing the PIP audio program in a portion of the display. However, the closed caption decoder in most television receivers processes only the caption information associated with the "main" picture, not the small picture signal.

An exception to this general rule can be found in certain television receivers manufactured by Sharp Corporation such as models 31H-X1200 and 35H-X1200. These Sharp television receivers display captions representing the audio of the PIP image by providing a switching capability that permits coupling the PIP signal to the main caption decoder. PIP captions are displayed full size (up to four rows of 32 large characters) at the top or bottom of the screen (a user selectable position). An example of PIP captioning produced by Sharp television receivers is shown in FIG. 1 which depicts a display including main image 100, PIP image 102 and PIP caption 104.

SUMMARY OF THE INVENTION

The invention resides, in part, in the inventors' recognition of a number of problems associated with the described PIP captioning implementation. First, main-picture captioning and small-picture captioning cannot be displayed simultaneously. Second, the small image combined with the caption display for the small image may obscure the

SUBSTITUTE SHEET (RULE 28)

main image to an extent that is objectionable to a user. For example, a PIP caption as in the Sharp implementation (up to 20% of the screen area) combined with a normal size PIP image (one-ninth of the screen area) may obscure more than 30% of the main video display. Third, the small-picture caption is difficult to follow simultaneously with small-picture video because the location of the caption at the top or bottom of the screen is physically disconnected from the small picture and may be a significant distance from the small picture. Fourth, the appearance of small-picture captions is virtually identical to main-picture captions causing users to become confused as to which image is associated with the caption. The combination of these problems may make auxiliary-picture captioning that is implemented in the manner described above objectionable to an extent that renders auxiliary-picture captioning useless for many viewers.

The invention also resides, in part, in providing apparatus and a method for solving the described problems associated with the prior art. More specifically, the present invention provides for positioning auxiliary information, such as closed captioning text characters, that is associated with an auxiliary picture in a multi-image display proximate the auxiliary picture. One aspect of the invention involves combining signals representing an auxiliary image, a border region for the auxiliary image, and auxiliary information with a signal representing the main image to produce a combined signal representing a composite image having the auxiliary information within the border region and proximate the auxiliary image. Another aspect of the invention involves producing a signal representing an image having first, second and third regions representing a main image, an auxiliary image and auxiliary information, respectively, and producing a change in the location of the second region such that the third region changes location in response to the change in location of the second region. Another aspect of the invention involves positioning the third region within the image for indicating to a user that the auxiliary information is associated with an auxiliary video program included in the second region. Another aspect of the invention involves a method of generating a multi-image display by combining main and auxiliary image signals with border and auxiliary information such that the auxiliary information is included within a border region and proximate the auxiliary image.

BRIEF DESCRIPTION OF THE DRAWING

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

Figure 1 depicts a PIP captioning orientation as implemented in the prior art;

Figure 2 depicts an orientation of auxiliary information relative to an auxiliary picture and a main picture in accordance with the present invention;

Figure 3 depicts circuitry for generating an exemplary small-picture caption in accordance with the present invention; and

Figures 4 and 5 illustrate various orientations of small-picture captioning with respect to a small image and to the main image.

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

DETAILED DESCRIPTION

For ease of description, the exemplary embodiments depicted in the drawing will be described in the context of a picture-in-picture (PIP) display system having a small auxiliary picture inset into a large main picture. However, the principles of the invention are applicable to other multi-image display systems such as a picture-outside-picture (POP) system in which an auxiliary picture located is located outside of, e.g., beside, the main picture.

FIG. 2 depicts the image orientation of a PIP image 202 in relation to a main picture 200 as produced by a PIP captioning image generation system of the present invention. The position of the PIP image 202 within the confines of the main picture 200 is conventionally defined by a viewer. Specifically, the viewer, through a remote control, defines a vertical line number (vertical position) and a pixel location (horizontal position) where one corner (e.g., upper left corner) of the PIP image is to be located. The active region 210 of the PIP image 202, where the PIP video is displayed, has a typical dimension of one third by one third of the size of the main picture 200. The PIP image area 210 (active region) is circumscribed by a border region 204. This border region is

approximately 0.25 inches (0.64 cm) wide. In the normal operating mode, e.g., without closed captioning, the border of the PIP image is approximately 0.25 inches wide on all sides of the active image area 210. Upon activation of the closed captioning for the PIP image, the bottom border area 206 is extended to a height of approximately 2 inches (5 cm). The closed caption information is displayed in this 2 inch wide region (referred to as a closed caption window) as two-lines of closed caption text 208. The invention provides a method and apparatus for producing information 208 within the extended border area 206 (i.e., position the caption for the PIP image proximate to the PIP active image area 210).

Although the depicted embodiment of the display positions the closed caption information for the PIP image at the bottom of the PIP image area, the PIP closed caption information could as easily be placed in an extended border area at the top of the PIP image area or anywhere else that is proximate the PIP image area 210.

FIG. 3 depicts circuitry 300 for positioning the PIP closed caption information proximate the active PIP image region as depicted in FIG. 2. The circuitry contains a main picture timing generator 312 coupled to a multiplexer array 314 and a PIP image generator 302. The multiplexer array contains three multiplexers 306, 308 and 310. These multiplexers are actively switched, on a pixel-by-pixel basis, to combine pixel values (e.g., luminance and color difference signals) and produce the images depicted in FIG. 2. Specifically, the third multiplexer 310 inserts the PIP image border and caption into the main picture; the second multiplexer 308 inserts the active PIP video imagery into the border region; and the first multiplexer combines closed caption character values with border values that forms a PIP captioning window.

More specifically, the timing generator 312 has as its input a vertical position 324 and a horizontal position 326 that is user defined for locating the PIP image within the boundaries of the main picture. For example, a user can determine the location of the PIP image by activating a "MOVE" key on a remote control. In a typical application, each activation of the MOVE key moves the PIP image to a different corner of the main display as indicated by the vertical and horizontal position values. The system shown in Figure 3 is controlled, for example, by a microcomputer (not shown in Figure 3). The microcomputer responds to

6

the user-selected PIP image position by generating two digital values representing the horizontal and vertical coordinates of the PIP position. The microcomputer stores the digital values in memory and, in a typical system, communicates the digital values to the system in Figure 3 via a data bus to provide vertical position 324 and horizontal position 326.

In addition to the horizontal and vertical position inputs, timing generator 312 receives vertical count 328 and horizontal count 330 as input signals. These count values indicate the present main picture line and pixel. The count values are generated in a conventional manner by counters (not shown in Figure 3) that count in response to timing signals including horizontal and vertical sync. Conventional sync signal generation circuitry (not shown in Figure 3) produces the sync signals in response to a composite sync component of a television signal.

In response to the count values, the timing generator produces three control signals, namely, CAPTION_INSERT, PIP_INSERT and FSW (FAST SWITCH). In general, these signals are timing signals that are active for certain portions (e.g., a predefined number of pixels) within certain lines. For example, the location for the caption within the main picture is defined by a number of inclusive lines and pixels. As such, for all count values that include these lines and pixels, the CAPTION_INSERT signal is active to define a rectangular caption window. The beginning of the window, e.g., its upper left corner, is defined as an offset of a number of lines and pixels from the vertical and horizontal position values (324 and 326) that define the location of the PIP image. The CAPTION_INSERT signal is coupled to closed caption generator 304 which generates signal INSERT CHARACTER VALUE on path 320 for controlling first multiplexer 306 as described further below.

Similarly, the PIP_INSERT and FSW signals are active for certain pixels and lines to control insertion of the active PIP image into the border region as well as insertion of the PIP image with its border and captioning into the main picture. Signal PIP_INSERT is also coupled to PIP generator 302 for defining where PIP generator 302 should position the PIP image pixels relative to the main picture.

The PIP image generator 302 contains a closed captioned character generator 304 that produces closed caption characters. Closed captioning standard EIA-608 specifies a closed caption character format comprising a display character grid of 15 rows by 32 columns with up to

SUBSTITUTE SHEET (RULE 28)

four rows of characters being displayed at any one time. Although these standard characters could be displayed proximate the image area of the PIP image using the present invention, the invention generally uses reformatted characters produced by character generator 302.

- 5 Reformatting performed by unit 304 comprises translating the standard closed caption character set into a reduced character set, utilizing a smaller font size, and displaying only two rows of 18 characters each within the PIP captioning window, e.g., the two-inch wide border extension. The reformatting facilitates viewer comprehension and
- 10 minimizes main picture obstruction. One example of a closed captioned character generator that provides reformatted characters is disclosed in United States Patent Application Serial No. 08/769,332 entitled "METHOD AND APPARATUS FOR REFORMATTING AUXILIARY INFORMATION INCLUDED IN A TELEVISION SIGNAL" which was filed in the name of
- 15 Mark F. Rümreich et al. on the same date as the present application, is commonly assigned, and is incorporated herein by reference.

- The PIP generator 302 produces a control signal INSERT CHARACTER VALUE on path 320 that is coupled to the control terminal of the first multiplexer 306. In addition to the control signal, the PIP
- 20 generator produces a PIP picture signal (ACTIVE PIP PIX) that is coupled to the second multiplexer 308. Using the PIP generator 302 and its accompanying closed caption character generator, the PIP picture or image as well as the closed-captioned data is extracted in a conventional manner from an auxiliary video signal (AUX VIDEO). Positioning of the
- 25 PIP image is controlled by the PIP_INSERT signal that is generated by the main picture timing generator 312, e.g., the PIP generator produces the PIP image pixels during a period when the PIP_INSERT signal is active. Furthermore, the timing generator 312 produces a CAPTION INSERT signal that is coupled to the closed-captioned character generator. This
- 30 signal controls the position of the closed-captioned window with respect to the main picture, e.g., the caption character pixels are positioned at pixels and lines where the CAPTION INSERT signal is active.

- The INSERT CHARACTER VALUE control signal (path 320) selects as the output of the first multiplexer either a character value 316
- 35 (e.g., a white level pixel value) or a border value 318 (e.g., a gray level pixel value). The result is an array of character values and border values, e.g., white pixels on a gray background, that when taken together as an

8

array of values depict one or more text characters on a gray background. The output of the first multiplexer 306 is coupled via path 322 to the first input of the second multiplexer 308. The output of the first multiplexer is essentially an image (a rectangular border layer) having a constant
 5 luminance value across the entire image except in a region where the closed captioned characters are inserted. The characters are located in a caption window defined by the CAPTION INSERT signal.

The second multiplexer 308 combines the active PIP image video with the border layer. As such, the second input of multiplexer 308
 10 is the active PIP image video (ACTIVE PIP PIX 332) produced by the PIP generator 302. The second multiplexer 308 is controlled by the PIP_INSERT signal produced by the timing generator 312. The timing generator 312 produces the PIP_INSERT signal to create the active PIP image area, e.g., a "high" signal during a number of pixels in each line that
 15 is to contain the PIP pix.

Specifically, the PIP_INSERT signal selects the first input to the second multiplexer for all vertical and horizontal count values outside of the active PIP image area. For all vertical and horizontal count values within that region, the PIP_INSERT signal selects the active PIP image
 20 video for output from the second multiplexer 308. As such, the active PIP video is inserted into the border layer proximate the PIP captioning window. A similar effect is accomplished if the first and second multiplexers are in reverse order, e.g., the active PIP image is combined with the border and then multiplexed with the character value.

25 Timing generator 312 includes conventional logic devices comprising, e.g., gates, flip-flops, etc. that generate active states on control signals CAPTION_INSERT, FSW, and PIP_INSERT during time intervals described above. The specific time intervals utilized in the exemplary embodiment are defined by the following relationships
 30 between horizontal count 330 (referred to below as "HC"), vertical count 328 ("VC"), horizontal position 326 ("HP"), and vertical position 324 ("VP"). Signal CAPTION_INSERT is active (e.g., high or logic 1) when:

35
$$4HP < HC < (4HP + 220); \text{ and}$$

$$(VP + 75) < VC < (VP + 72 + 18CAP).$$

SUBSTITUTE SHEET (RULE 26)

9

That is, signal CAPTION_INSERT is active when HC is greater than 4HP and less than $4HP + 220$, and VC is greater than $(VP+75)$ and less than $(VP + 72 + 18CAP)$ where "CAP" is a binary value (either 1 or 0) indicating whether PIP captioning is enabled. That is, when a user enables PIP captioning, e.g., by selecting "PIP CAPTIONING ON" from a setup menu, CAP has a value of 1. Similarly, signal FSW is active when:

$$4HP < HC < (4HP + 232); \text{ and} \\ VP < VC < (VP + 75 + 18CAP);$$

10

Signal PIP_INSERT is active when:

$$4HP < HC < (4HP + 22); \text{ and} \\ (VP + 3) < VC < (VP + 72).$$

15

Values such as the 4 that is multiplied times HP and the 220 that is added to HP define horizontal offsets (e.g., in pixels) that control the horizontal position and width of the border, PIP image and PIP caption windows. Similarly, values that are added to VP define vertical offsets (e.g., in lines) that control the vertical position and height of the border, PIP image, and PIP caption windows. It will be apparent that these offset values can be modified to vary the position and size of the windows as needed.

20

Regardless of the ordering of the first and second multiplexers, the system provides for keeping the PIP captioning in close proximity to the PIP image. If the location of the PIP image changes, for example, when the user moves the PIP image (such as using the above-mentioned "MOVE" key on a remote control), the location of the PIP caption moves automatically to remain in close proximity to the PIP image. That is, the location of the PIP captioning is determined in response to the location of the PIP image. Figure 4 illustrates four exemplary locations of a PIP image and an exemplary orientation of the PIP captioning for each PIP image location. A variation of the arrangement of Figure 4 is illustrated in Figure 5 in which PIP captioning automatically changes its orientation with respect to the main image and moves within the border layer. For example, moving the PIP image from a top portion of the main image to a bottom portion of the main image causes the PIP captioning to move within the border as shown in Figures

30

35

SUBSTITUTE SHEET (RULE 20)

10

5A and 5B or as shown in Figures 5C and 5D. Moving the PIP captioning within the border layer can, for example, improve readability of the PIP captioning and/or minimize interference of the PIP captioning with the main image. The particular manner in which the PIP captioning moves 5 within the border layer can be selected by a user from a setup menu.

Returning to Figure 3, a third multiplexer 310 selects between the PIP image with its border layer and the main picture 334. The third multiplexer 310 is driven by a fast switch (FSW) signal generated by the timing generator 312. The FSW signal selects the first input to the third 10 multiplexer 310 (the PIP image and border) for all horizontal and vertical count values within the PIP image area including the border region. For all vertical and horizontal count values outside of the image and border region for the PIP image, the FSW signal selects the main picture. As such, the PIP image and its border layer is inserted into the main picture 15 and the FSW signal defines the width of the border. The signals at the output of the multiplexer 310 are coupled to a display driver (not shown but well known in the art).

Using the circuitry of FIG. 3, the display of FIG. 2 is produced. The circuitry, in essence, uses a layered approach to image generation. 20 Specifically, a closed caption text character value is combined with a border value to produce a border layer (a gray layer having a predefined size and containing closed caption text), then the active PIP pix is combined with the border layer, and lastly, the main pix is multiplexed with the PIP image, its border and text to create the comprehensive PIP 25 display of FIG. 2. Because the system provides for locating the closed-caption text in close proximity to the PIP image, a viewer can easily comprehend the closed caption text in reference to the PIP image.

Although various embodiments which incorporate the teachings of the present invention have been shown and described in 30 detail herein, those skilled in the art can readily devise many other varied embodiments that still incorporate these teachings. For example, various configurations of the border region shown in Figure 2 are possible. First, various orientations of the border region are possible as discussed above and shown in Figures 4 and 5. In addition, the border 35 region extension containing the auxiliary information can be adjacent to the PIP image as shown in Figures 2, 4 and 5 or can be located spaced

SUBSTITUTE SHEET (RULE 26)

11

slightly from the PIP image, e.g., with a region of different color and/or brightness.

SUBSTITUTE SHEET (RULE 20)

12
CLAIMS:

1. Apparatus comprising:
means for processing (302) a first television signal for
5 generating a first signal representing auxiliary information included in
said first television signal;
means for generating a control signal (312); and
means responsive to said control signal for combining
(306,308,310) said first signal, a signal representing an auxiliary image, a
10 signal representing a border region for said auxiliary image and a second
television signal representing a main image to produce a combined signal
representing a composite image including said main image, said auxiliary
image, said border region and said auxiliary information such that said
auxiliary information is displayed within said border region and
15 proximate said auxiliary image.
2. The apparatus of claim 1 wherein said auxiliary
information comprises text.
- 20 3. The apparatus of claim 2 wherein said text comprises
closed caption information.
4. The apparatus of claim 1 wherein
said means for combining signals comprises a multiplexer;
25 said control signal generating means comprises a timing
generator and said control signal comprises a timing signal for causing
said multiplexer to include said first signal, said signal representing said
auxiliary image, and said signal representing said border region in said
combined signal such that said auxiliary information is displayed within
30 said border region and proximate said auxiliary image.
5. The apparatus of claim 4 wherein said signal
representing said border region comprises border values; said auxiliary
information comprises closed caption information; said multiplexer array
35 combines said border values with said closed caption information to
produce a border layer, combines said signal representing said auxiliary
image with said border layer to produce an intermediate signal, and

SUBSTITUTE SHEET (RULE 26)

13

combines said intermediate signal with said signal representing said main image to produce said combined signal.

6. The apparatus of claim 4 wherein said signal
5 representing said border region comprises a border value; said auxiliary information comprises a closed caption character value; said multiplexer comprises:
- a first multiplexer (306) for combining said border value with said closed caption character value to produce a border layer
10 representing said border region including said auxiliary information;
a second multiplexer (308), coupled to said first multiplexer, for combining said signal representing said auxiliary image with said border layer to produce an intermediate signal; and
a third multiplexer (310), coupled to said second multiplexer,
15 for combining said intermediate signal with said signal representing said main image.

7. The apparatus of claim 6 wherein said timing generator produces said control signal for said multiplexer in response to a user
20 defined horizontal and vertical coordinate position (324,326) for said auxiliary image, a vertical count value and a horizontal count value, where the horizontal and vertical count values (328,330) indicate a particular pixel location being displayed in said main image.

- 25 8. The apparatus of claim 7 wherein said auxiliary image comprises a PIP image or a POP image.

9. Apparatus comprising:
means for extracting (302) auxiliary information from an
30 auxiliary video signal;
means for processing (306,308,310) a main video signal and said auxiliary video signal for generating an output signal representing a video image having a first region representing a main video program included in said main video signal, having a second region representing
35 an auxiliary video program included in said auxiliary video signal, and having a third region representing said auxiliary information; and

SUBSTITUTE SHEET (RULE 28)

14

means for producing (312) a change in location of said second region within said video image; said third region exhibiting a change in location within said video image in response to said change in location of said second region.

5

10. The apparatus of claim 9 wherein said third region being located proximate said second region before and after said change in location of said second region.

10

11. The apparatus of claim 10 wherein said second and third regions being located in said video image with a first orientation before said change in location of said second region; said first orientation being maintained following said change in location of said second region.

15

12. The apparatus of claim 10 wherein said second and third regions being located in said video image with a first orientation before said change in location of said second region; said first orientation changing to a second orientation following said change in location of said second region.

20

13. Apparatus comprising:

means for extracting (302) auxiliary information from an auxiliary video signal;

means for processing (306,308,310) a main video signal and said auxiliary video signal for generating an output signal representing a video image having a first region representing a main video program included in said main video signal, having a second region representing an auxiliary video program included in said auxiliary video signal, and having a third region representing said auxiliary information; and

30

means for positioning (312) said third region in said video image for indicating to a user that said auxiliary information is associated with said auxiliary video program included in said second region.

14. The apparatus of claim 13 wherein said means for positioning said third region also positions said second region in said video image; said means for positioning said second and third regions being responsive to a user input for producing a change in position of said

SUBSTITUTE SHEET (RULE 26)

15

second and third regions; said third region being positioned subsequent to said change in position such that said user associates said auxiliary information with said auxiliary video program subsequent to said change in position.

5

15. The apparatus of claim 14 wherein said second region of said video image represents a PIP image or a POP image.

16. A method for generating a multi-image display having
10 character information located proximate an auxiliary image within a main picture, comprising the steps of:

extracting (302) auxiliary information from an auxiliary video signal representing said auxiliary image;

combining (306) a border value with said auxiliary
15 information to produce a border layer containing said auxiliary information;

combining (308) said auxiliary video signal with said border layer to produce an intermediate signal representing said auxiliary image, a border region and said auxiliary information located proximate said
20 auxiliary image and within said border region; and

combining (310) said intermediate signal and a main video signal representing said main picture.

1/4




FIG. 1
PRIOR ART




FIG. 2

SUBSTITUTE SHEET (RULE 28)




FIG. 3

3/4

FIG. 4A




FIG. 4B




FIG. 4C





FIG. 4D



SUBSTITUTE SHEET (RULE 28)

4/4

FIG. 5A




FIG. 5B




FIG. 5C





FIG. 5D



SUBSTITUTE SHEET (RULE 28)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/22750

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 H04N5/45		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 H04N		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 401 930 A (PHILIPS NV) 12 December 1990 see column 12, line 39 - line 57; figures 11A, 14A ---	1
A	EP 0 301 488 A (SANYO ELECTRIC CO) 1 February 1989 see column 24, line 25 - column 25, line 44; figure 22 ---	1, 9, 13, 16
A	GB 2 232 033 A (SAMSUNG ELECTRONICS CO LTD) 28 November 1990 see page 10, line 14 - line 27; figure 2A --- -/--	1, 9, 13, 16
<div style="display: flex; justify-content: space-between;"> <input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex. </div>		
* Special categories of cited documents :		
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search <div style="text-align: center; font-weight: bold;">8 April 1998</div>		Date of mailing of the international search report <div style="text-align: center; font-weight: bold;">20/04/1998</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer <div style="text-align: center; font-weight: bold;">Yvonnet, J</div>

INTERNATIONAL SEARCH REPORT

Int. onal Application No
PCT/US 97/22750

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 001, 31 January 1996 & JP 07 236100 A (VICTOR CO OF JAPAN LTD), 5 September 1995, see abstract ---	1,9,13, 16
P,X	EP 0 762 751 A (HITACHI LTD) 12 March 1997 see column 14, line 38 - line 42; figures 15,25B ---	1,13,16
A	EP 0 660 602 A (TOKYO SHIBAURA ELECTRIC CO) 28 June 1995 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/22750

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0401930 A	12-12-90	US 5047867 A	10-09-91
		AT 116501 T	15-01-95
		CN 1049436 A, B	20-02-91
		CS 9002776 A	12-11-91
		DE 69015454 D	09-02-95
		DE 69015454 T	13-07-95
		ES 2068991 T	01-05-95
		HK 75596 A	10-05-96
		JP 3101485 A	26-04-91
EP 0301488 A	01-02-89	JP 1157176 A	20-06-89
		JP 2698105 B	19-01-98
		US 4982279 A	01-01-91
GB 2232033 A	28-11-90	US 5623346 A	22-04-97
EP 0762751 A	12-03-97	JP 9065224 A	07-03-97
EP 0660602 A	28-06-95	JP 7184135 A	21-07-95
		CN 1115453 A	24-01-96
		US 5671019 A	23-09-97